



Made in China. Proudly assembled in USA


BOW WEIGHT/LBS.	ARROW LENGTH											
	24	25	26	27	28	29	30	31	32	33	34	35
32-36	600	600	600	600	500	500	500	400	400	400	400	400
37-41	600	600	600	500	500	500	400	400	400	400	400	400
42-46	600	600	500	500	500	400	400	400	350	350	350	350
47-51	600	500	500	500	400	400	400	350	350	350	350	350
52-56	500	500	500	400	400	400	350	350	350	350	350	350
57-61	500	500	400	400	400	350	350	350	300	300	300	300
62-66	500	400	400	400	350	350	350	300	300	300	300	300
67-72	400	400	400	350	350	350	300	300	300	300	300	300
73-78	400	400	350	350	350	300	300	300	250	250	250	250
79-84	400	350	350	350	300	300	300	250	250	250	250	250
85-90	350	350	350	300	300	300	250	250	250	250	250	250

HARD IMPACT TECHNOLOGIES

THE ONLY WEIGHT TRANSFERRING TECHNOLOGY ARROW SHAFT™

WEIGHT TRANSFERS ON IMPACT

www.HARDIMPACTTECH.COM



Contains 10 Hunting Shafts and 2 static weight practice shafts

■ 250 ■ 300 ■ 350 ■ 400 ■ 500 ■ 600

Straightness: +/- .003

Point Arrow tip up to engage prior to use. **DO NOT MISUSE. WARNING!** Inspect Arrow Shaft prior to use. Patent Pending.



Made in China. Proudly assembled in USA


BOW WEIGHT/LBS.	ARROW LENGTH											
	24	25	26	27	28	29	30	31	32	33	34	35
32-36	600	600	600	600	500	500	500	400	400	400	400	400
37-41	600	600	600	500	500	500	400	400	400	400	400	400
42-46	600	600	500	500	500	400	400	400	350	350	350	350
47-51	600	500	500	500	400	400	400	350	350	350	350	350
52-56	500	500	500	400	400	400	350	350	350	350	350	350
57-61	500	500	400	400	400	350	350	350	300	300	300	300
62-66	500	400	400	400	350	350	350	300	300	300	300	300
67-72	400	400	400	350	350	350	300	300	300	300	300	300
73-78	400	400	350	350	350	300	300	300	250	250	250	250
79-84	400	350	350	350	300	300	300	250	250	250	250	250
85-90	350	350	350	300	300	300	250	250	250	250	250	250

HARD IMPACT TECHNOLOGIES

THE ONLY WEIGHT TRANSFERRING TECHNOLOGY ARROW SHAFT™

WEIGHT TRANSFERS ON IMPACT

www.HARDIMPACTTECH.COM



Contains 10 Hunting Shafts and 2 static weight practice shafts

■ 250 ■ 300 ■ 350 ■ 400 ■ 500 ■ 600

Straightness: +/- .003

Point Arrow tip up to engage prior to use. **DO NOT MISUSE. WARNING!** Inspect Arrow Shaft prior to use. Patent Pending.

AMPHIBATOR

AMPHIBATOR